



Ecoglo "Exit Double Arrow" S20 Signs are designed to clearly mark the direction of travel to the nearest exit. The signs will be clearly visible and readily understandable under all conditions of foreseeable use, including emergency conditions.

SIGN DEFINITION

Exit right or left from here.

UL 924 LISTED

Ecoglo "Exit Double Arrow" S20 signs are UL 924 tested and listed.
UL Product File No: E516232

COMPLIANCE

Ecoglo "Exit Double Arrow" S20 signs are UL924 tested to meet viewing distances of 50 feet (15.24 metres) and 75 feet (22.86 metres) for compliance with NFPA 101 Life Safety Code, IFC and any other performance based building codes.

PERFORMANCE

The signs will be operational for at least 90 minutes after failure of the main lighting provided they have been continuously illuminated by a reliable light source with a minimum of 5 ft-candles (54 lux).

Operating Temperature Range: -20°C to +40°C*

* For controlled environment (constant temperature) rooms below 0°C contact Ecoglo.

Luminance - S20 grade signs easily exceed PSPA class G

UV Resistance - Loss of luminance after 1000 hrs ASTM G-155
Cycle 1 exposure: <10%

Salt Spray Resistance – ASTM B117: Pass

Washability – ASTM D4828: Pass

Rate of Burning – ASTM D635: Pass

Surface Flammability - ASTM E162: Pass

Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass

High Temperature Curing: Pass

COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in

thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature.



INSTALLATION

Signs are supplied with fixers for mounting flat on a wall. Brackets for ceiling or flag mounting are also available.

ORDERING

The product is available in 2 sizes to meet viewing distances of 50 feet (15.24 metres) and 75 feet (22.86 metres).

PRODUCT CODE	PRODUCT	SIGN SIZE	MAXIMUM VIEWING DISTANCE
S20-UL-EXRL353183-50	Exit Double Arrow	353mm x 183mm	50 feet (15.24m)
S20-UL-EXRL481249-75	Exit Double Arrow	481mm x 249mm	75 feet (22.86m)
Mounting Brackets (Take one sign or two signs back to back)			
BR1-353	Ceiling Mount Bracket for S20-UL-EXRL353183-50		
BR1-481	Ceiling Mount Bracket for S20-UL-EXRL481249-75		
BR1-183	Flag Mount Bracket for S20-UL-EXRL353183-50		
BR1-249	Flag Mount Bracket for S20-UL-EXRL481249-75		

Chain suspension is also available.

Contact

Ecoglo International Limited

Email: info@ecoglo.com **Web:** www.ecoglo.com