
Product Data Sheet - Guidance Strip G3-001

2022 V1






The G3-001 Guidance Strip is designed to ensure visibility of specified building features in escape routes for compliance with NFPA 101 Life Safety Code (NFPA 101) and International Fire Code (IFC), and any performance based building codes. The Guidance Strip will be effective in all light conditions including during failure of the main lighting.

COMPLIANCE

Tested to UL 1994 specifications to meet the requirements of NFPA 101 and IFC. This product has also been independently tested for use in Performance Solutions to meet the performance requirements of any performance based building codes.

The Guidance Strip is suitable for use indoors and outdoors.





Operating Temperature Range: -10°C to +40°C*

* For controlled environment (constant temperature) rooms below 0°C contact Ecoglo.

UV Resistance - Loss of luminance after 1000 hrs ASTM G-155

Cycle 1 exposure: <10%

Salt Spray Resistance – ASTM B117: Pass

Washability –ASTM D4828: Pass Rate of Burning – ASTM D635: Pass Surface Flammability - ASTM E162: Pass

Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass High Temperature Curing: Pass

SUPPLY

The product is available in 1 metre lengths and 3.06 metre lengths.

COMPOSITION

Ecoglo G3-001 Guidance Strip is manufactured from extruded 6063T5 aluminium section. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients into the aluminium following curing at high temperature.

The photoluminescent area is also recessed into protective channels.

INSTALLATION

Installation needs to be carried out strictly in accordance with the Ecoglo installation instructions.

Consult Installation Instructions on website for full details and surface preparation.

Fixers (screws) can be used if adhesion is difficult. (See order codes below for the product that best suits).

G3-001-1000 For polyurethane adhesive fixing G3-001-3060 For polyurethane adhesive fixing G3-001P-1000 Punched for screw fixing G3-001P-3060 Punched for screw fixing G3-001T-1000 Release tape pre-fitted

G3-001T-3060 Release tape pre-fitted

Contact

Ecoglo International Limited

Email: info@ecoglo.com Web: www.ecoglo.com