



315mm x 290mm



588mm x 475mm



950mm x 588mm



1190mm x 980mm



2380mm x 980mm

Please note graphics above are examples only. Customisation of the artwork is available for different provinces, regions or offices. Contact Ecoglo for more information.

Ecoglo S20 Landslide Warning signs are designed to be used to warn persons of the danger of landslides in the area. The signs will be clearly visible and readily understandable under all conditions of foreseeable use, including darkness.

SIGN DEFINITION

Danger of landslides.

PERFORMANCE

Ecoglo S20 Landslide Warning signs will absorb enough natural daylight to remain visible throughout the night.

Luminance – S20 grade signs easily exceed PSPA class G

UV Resistance – Loss of luminance after 1000 hrs ASTM G-155

Cycle 1 exposure: <10% Salt Spray Resistance – ASTM B117: Pass

Salt Spray Resistance – ASTM B117: Pass

Washability – ASTM D4828: Pass

Rate of Burning - ASTM D635: Pass

Surface Flammability – ASTM E162: Pass

Toxicity – Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity – ASTM D3648: Pass

SUPPLY

The sign is available in sizes listed – see product order codes below.

PRODUCT CODE	PRODUCT NAME	SIGN DEFINITION	SIGN SIZE
S20-LS315290	Landslide Warning	Danger of landslides	315mm x 290mm
S20-LS588475	Landslide Warning	Danger of landslides	588mm x 475mm
S20-LS950588	Landslide Warning	Danger of landslides	950mm x 588mm
S20-LS1190980	Landslide Warning	Danger of landslides	1190mm x 980mm
S20-LS2380980	Landslide Warning	Danger of landslides	2380mm x 980mm

COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature – a process known as HTC.



This sign also has HTC Clear Coating added to protect the print in outdoor environments.

INSTALLATION

The sign should be installed using fixers (screws). Please note the sign is supplied without drill holes.

Contact

Ecoglo International Limited

Email: info@ecoglo.com Web: www.ecoglo.com