



**Ecoglo S5 Fire Extinguisher Sign is designed to be used in and about buildings, structures and facilities to identify the location of fire extinguishers. The sign will be readily and clearly visible along normal paths of travel, including exits.**

#### SIGN DEFINITION

Fire extinguisher located here.

#### COMPLIANCE

Ecoglo S5 "Fire Extinguisher" signs meet luminance specifications of internationally accepted UL 1994 Standard for Luminous Egress Path Marking Systems.

#### PERFORMANCE

The signs will be operational for up to 90 minutes after failure of the main lighting provided they have been continuously illuminated by a reliable light source with a minimum of 54 lux.

**Luminance** – S5 grade signs easily exceed PSPA class D

**UV Resistance** – Loss of luminance after 1000 hrs ASTM G-155 Cycle 1 exposure: <10%

**Salt Spray Resistance** – ASTM B117: Pass

**Washability** – ASTM D4828: Pass

**Rate of Burning** – ASTM D635: Pass

**Surface Flammability** – ASTM E162: Pass

**Toxicity** – Bombardier Toxic Gas Generation Test SMP800-C: Pass

**Radioactivity** – ASTM D3648: Pass

#### SUPPLY

The sign is available in one size only – see product order code below.

PRODUCT CODE	PRODUCT NAME	SIGN DEFINITION	SIGN SIZE
S5-FEXT2010	Fire Extinguisher	Fire Extinguisher located here	200mm x 100mm

#### COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature - a process known as HTC.



#### INSTALLATION

For versatility the sign can be installed using fixers (screws) or double-sided adhesive tape. Please note the sign is supplied without drill holes or tape.

**Note:** The installation method used should be determined by the condition of the installation surface - screws should be used if there is any doubt about adhesion.

#### Contact

**Ecoglo International Limited**

**Email:** info@ecoglo.com **Web:** www.ecoglo.com